

Technical data sheet

Quarzsand

Quartz sand in different grain sizes

Areas of application

Quarzsand is a mixture of fire-dried quartz sands for spreading primers and intermediate layers or as a filler for:

- Thin-layer synthetic resin mortar
- Thick-layer synthetic resin mortar
- Repair filler

Properties

Quartz sand grain sizes:

- 0.1-0.3 mm
- 0.1-0.6 mm
- 0.3-0.9 mm
- 0.7-1.2 mm

Coverage

Depending on application

Delivery form

- 25 kg in a bag

Storage

Store unopened and in a dry place.

Processing

Application

Quartz sand for sprinkling or working into primers and coatings.

Tools and aids



General information

The product must not be mixed and processed with other substances not belonging to the system. No materials other than those specified by FRANKEN SYSTEMS GmbH are permitted to be used.

Miscellaneous

It's to the best of our knowledge that we've provided the above information as well as our technical advice on applications, whether verbal, in writing or by means of tests. However, this information shall only be regarded as non-binding, which also applies to any property rights of third parties. The advice does not release you from examining our current advisory notes yourself (our safety data sheets and technical information in particular) and our products with regard to their suitability for the intended processes and purposes. The application, use and



Additional product

processing of our products as well as the intended use selected by you on the basis of our technical application-specific advice are beyond our control and are therefore exclusively your responsibility. The sale of our products is subject to our current General Terms and Conditions of Sale and Delivery. Warnings on the product labels must be observed. The latest version of the applicable documents shall be used.

Please check that the documents used are up-to-date and/or request an up-to-date document before each application.